




DOWANOL PM

Propylene Glycol Methyl Ether



A fast-evaporating, hydrophilic glycol ether with excellent active solvency and coupling abilities

Introduction

DOWANOL* PM glycol ether is the fastest evaporating solvent in the DOWANOL glycol ether family. With very high water solubility and active solvency, DOWANOL PM glycol ether is widely used in coating and cleaning applications. It offers better viscosity reduction than heavier molecular weight glycol ethers and is particularly effective in epoxy and high solids acrylic systems. DOWANOL PM can also be used in combination with DOWANOL PnB glycol ether in glass cleaning formulations.

Physical properties†

Molecular weight (g/mol)		90.1
Boiling point @ 760 mmHg, 1.01 bar	248°F	120°C
Flash point (Setaflash Closed Cup)	88°F	31°C
Freezing point	-143°F	-97°C
Vapor pressure@ 20°C — extrapolated		8.7 mmHg 11.6 mbar
Specific gravity (25/25°C)		0.919
Density @ 20°C	7.69 lb/gal	0.921 g/cm ³
@ 25°C	7.65 lb/gal	0.916 g/cm ³
Viscosity (cP or mPas @ 25°C)		1.7
Surface tension (dynes/cm or mN/m @ 25°C)		27.7
Specific heat (J/g°C @ 25°C)		2.44
Heat of vaporization (J/g) at normal boiling point		435
Net heat of combustion (kJ/g) — predicted @ 25°C		24.7
Autoignition temperature	549°F	287°C
Evaporation rate	(n-butyl acetate = 1.0) (diethyl ether = 1.0)	0.62 20
Solubility, g/100 g @ 25°C		
Solvent in water		∞
Water in solvent		∞
Hansen solubility parameters (J/cm ³) ^{1/2}		
_d (Dispersion)		15.6
_p (Polar)		7.2
_h (Hydrogen bonding)		13.6

Flammable limits (vol.% in air)	
Lower (measured @ 150°C)	1.48
Upper (measured @ 150°C)	13.74

†The physical property data listed here are considered to be typical properties, not specifications.

Classification/Registry Numbers††

CAS Number	107-98-2
AICS (Australia)	107-98-2
DSL (Canada)	107-98-2
ECL (Korea)	2-343
EINECS (EU)	203-539-1
MITI (Japan)	2-404
TSCA (U.S.)	107-98-2

†† **NOTE:** Classifications apply only to this glycol ether product. It is the responsibility of the formulator to ensure that the final finished product complies with the regulations of a given country prior to its sale or distribution in that country.

Suggested Applications

- Active solvent for solvent-based coatings.
- Active and tail solvent for solvent based gravure and flexographic printing inks.
- Coupling agent in solvent blends for water-based gravure, flexographic, and silk screen printing inks.
- Carrier solvent for ball point and felt tip writing pen inks.
- Coupling agent and solvent for household and industrial cleaners, rust removers, and hard surface cleaners.
- Solvent for agricultural pesticides, deactivator and emollient for livestock pesticides.

Features

- Powerful solvency
- Moderate evaporation rate
- Low viscosity
- High dilution ratio
- Low surface tension
- Coupling ability
- Wide range of applications

NOTE: Consult the appropriate Material Safety Data Sheet for safety and handling guidelines for this product.

*The Dow Chemical Company
Midland, Michigan 48674 U.S.A.

In The United States And Canada:
1-800-447-4369
Fax: 1-989-832-1465

In Europe: +800 3 694 6367
Toll Phone: +32 3 450 2240
Toll Fax: +32 3 450 2815

In The Pacific: +800 7776 7776
Fax: +800 7779 7779
In Other Global Areas: 1-989-832-1556
Fax: 1-989-832-1465

Notice: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

Published March 2004

