



Diisobutyl Carbinol

2,6-Dimethyl-4-heptanol

Nonyl Alcohol

Dimethyl Heptanol

C₉H₁₉OH

Description

A transparent, colorless liquid with a sweet odor.

Physical properties

Molecular Weight	144.26
Relative Evaporation Rate nBuAc=1	0.02
Vapor Pressure at 20°C, mmHg	0.1
Density at 20°C lb/gal	6.75
Specific Gravity at 20/20°C	0.811
Viscosity at 20°C cP	15.4
Surface Tension	
(dynes/cm at 20°C)	26.0
(dynes/cm at 25°C)	-
Hansen Solubility Parameters	
Total	9.0
Non-Polar	7.3
Polar	1.4
Hydrogen Bonding	5.2
Boiling Point, °C at 760mm Hg	178.0
Solubility at 20°C	
%Wt In Water	0.06
%Wt Water in	1.0
Closed Cup Flash Point °F	149
SARA 313 (see note 1†)	N
Hazardous Air Pollutant (see note 2††)	N

† **Note 1:** Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III Section 313

†† **Note 2:** Hazardous Air Pollutants listed under Title III of the Clean Air Act

Classification/Registry Numbers

CAS Number	108-82-7
EINECS	203-61-6

(Please see second page)

Diisobutyl Carbinol

2,6-Dimethyl-4-heptanol

Nonyl Alcohol

Dimethyl Heptanol

Features

- Secondary alcohol with steric hinderance
- Very slightly soluble in wter
- Miscible with most orgnic solvents
- High boiling-point, slow-evaporating solvent
- Low surface tension
- Non-HAP (Hazardous air pollutant) Solvent

Applications

- Extraction solvent for acetic acid and ethanol from aqueous solution
- Extraction solvent for ethyl acetate from methyl ethyl ketone
- Extraction solvent for neptunium, niobium, protactinium, and zirconium-88
- Flotation agent
- Formation of ester gums for varnish
- Solvent for hydrogen peroxide manufacture, lacquers, shellac, printing inks, vinyl-chloride-acetate resins, urea-melamine resins and alkyd resins
- Refining solvent for petroleum products
- Rubber additive, plasticizer, and surface active agent
- Palladium-catalyzed oxidation to MIBK
- Alkylation by salicylic acid esters
- Chemical intermediate for dyestuffs, perfume manufacture, pesticides, pharmaceuticals, lubricants and oil additives

How supplied

- Bulk tank truck
- Drums

Special handling

Risk phrase R10 (Flammable)
R37 (Irritant to respiratory system)
Safety phrase S24 (Avoid contact with skin)

Note: Consult the appropriate Material Safety Data Sheet for safety and handling guidelines for this product.

The Dow Chemical Company
Danbury, Connecticut 06817 U.S.A.

In the United States and Canada, Product Information: 1-800-447-4369; Fax: 1-989-832-1465; Technical Support: 1-800-SOLVENT
In Europe: +800 3 694 6367; Toll Phone: +32 3 450 2240; Toll Fax: +32 3 450 2815
In the Pacific: +800 7776 7776; Fax: +800 7779 7779
In Other Global Areas: 1-989-832-1556; Fax: 1-989-832-1465

NOTICE: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

