




Primary Amyl Alcohol

Pentanol Mixture
Pentyl Alcohol Mixed
Amyl Alcohol



Description

Colorless liquid with a mild and characteristic odor. Miscible with common organic solvents.

Physical properties

| | |
|--|-------|
| Molecular Weight | 88.15 |
| Relative Evaporation Rate nBuAc=1 | 0.25 |
| Vapor Pressure at 20°C, mmHg | 2.2 |
| Density at 20°C lb/gal | 6.79 |
| Specific Gravity at 20/20°C | 0.815 |
| Viscosity at 20°C cP | 4.3 |
| Surface Tension | |
| (dynes/cm at 20°C) | 23.7 |
| (dynes/cm at 25°C) | - |
| Hansen Solubility Parameters | |
| Total | 10.6 |
| Non-Polar | 7.8 |
| Polar | 2.2 |
| Hydrogen Bonding | 6.8 |
| Boiling Point, °C at 760mm Hg | 133.2 |
| Solubility at 20°C | |
| %Wt In Water | 1.7 |
| %Wt Water in | 9.2 |
| Closed Cup Flash Point °F | 113 |
| SARA 313 (see note 1†) | N |
| Hazardous Air Pollutant (see note 2††) | N |

† **Note 1:** Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III Section 313

†† **Note 2:** Hazardous Air Pollutants listed under Title III of the Clean Air Act

Classification/Registry Numbers

| | |
|------------|----------------------|
| CAS Number | 137-32-6; 71-41-0 |
| EINECS | 205-289-9; 200-752-1 |

(Please see second page)

Primary Amyl Alcohol Pentanol Mixture Pentyl Alcohol Mixed Amyl Alcohol

Features

- Good solvency
- Lower volatility
- Available hydroxyl functionality on alkyl chain
- Slightly soluble in water
- Miscible with common organic solvents
- Non-HAP (Hazardous Air Pollutant) Solvent

Applications

- Intermediate
- Coating solvent
- Amyl xanthate for mining
- Lube oil additive
- Extraction solvent

How supplied

- Bulk: Tank trucks/tank cars/isotanks/marine vessel
- Drums

Note: Consult the appropriate Material Safety Data Sheet for safety and handling guidelines for this product.

The Dow Chemical Company
Danbury, Connecticut 06817 U.S.A.

In the United States and Canada, Product Information: 1-800-447-4369; Fax: 1-989-832-1465; Technical Support: 1-800-SOLVENT
In Europe: +800 3 694 6367; Toll Phone: +32 3 450 2240; Toll Fax: +32 3 450 2815
In the Pacific: +800 7776 7776; Fax: +800 7779 7779
In Other Global Areas: 1-989-832-1556; Fax: 1-989-832-1465

NOTICE: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

