



# UCAR™ Ester EEP

## Ethyl 3-Ethoxypropionate



### Description

UCAR™ Ester EEP is a slow evaporating ether-ester solvent with excellent solvent properties for a wide range of coating applications. It provides excellent film formation due to its enhanced flow and leveling characteristics.

### Physical properties

Molecular Weight	146.19
Relative Evaporation Rate nBuAc=1	0.1
Vapor Pressure at 20°C, mmHg	0.7
Density at 20°C lb/gal	7.91
Specific Gravity at 20/20°C	0.951
Viscosity at 20°C cP	1.3
Surface Tension	
(dynes/cm at 20°C)	28.1
(dynes/cm at 25°C)	-
Hansen Solubility Parameters, [cal/cm <sup>3</sup> ] <sup>1/2</sup>	
Total	9.1
Non-Polar	7.9
Polar	1.6
Hydrogen Bonding	4.3
Boiling Point, °C at 760mm Hg	169.7
Solubility at 20°C	
%Wt In Water	5.2
%Wt Water in	2.2
Closed Cup Flash Point °F	138
SARA 313 (see note 1†)	N
Hazardous Air Pollutant (see note 2††)	N
Electrical Resistivity MΩ	>1000

† **Note 1:** Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III Section 313

†† **Note 2:** Hazardous Air Pollutants listed under Title III of the Clean Air Act

### Classification/Registry Numbers

CAS Number	763-69-9
EINECS	212-112-9

(Please see second page)

# UCAR™ Ester EEP

## Ethyl 3-Ethoxypropionate

### Features

- Moderate odor
- High boiling point
- Low surface tension
- High electrical resistance
- Slow evaporation rate
- High solvency for a wide range of polymers
- Excellent retarder characteristics
- Ether-Ester functionality
- Excellent solvent release from coating films
- Low solution viscosity
- Excellent flow & leveling
- Non-HAP (Hazardous Air Pollutant) Solvent

### Applications

- High solids coatings
- Electrostatically sprayed coatings
- Conventional enamels and lacquers
- Acrylic polymerization

### How supplied

Region	Packaging	Transport Mode
Europe/Africa	Bulk or Drum	Isotank/Marine Vessel/Tank Truck/Package Truck
Latin America	Bulk or Drum	Isotank/Package Truck/Marine Vessel Tank Truck & Railcar (Mexico Only)
North America	Bulk or Drum	Tank Truck/Package Truck/Railcar
Pacific	Bulk or Drum	Tank Truck/Package Truck /Marine Vessel

Note: Consult the appropriate Material Safety Data Sheet for safety and handling guidelines for this product.

**The Dow Chemical Company**  
Danbury, Connecticut 06817 U.S.A.

**In the United States and Canada, Product Information: 1-800-447-4369; Fax: 1-989-832-1465; Technical Support: 1-800-SOLVENT**  
**In Europe: +800 3 694 6367; Toll Phone: +32 3 450 2240; Toll Fax: +32 3 450 2815**  
**In the Pacific: +800 7776 7776; Fax: +800 7779 7779**  
**In Other Global Areas: 1-989-832-1556; Fax: 1-989-832-1465**

NOTICE: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

